


The practical and versatile **GRANITE 400 series** can be used for both indoor and outdoor applications. The weather-resistant cabinets, made of glass-reinforced polypropylene, can easily be installed around the house and throughout the garden. All models are available in black or white, to suit any decor and can be wall or ceiling mounted using the supplied brackets.



All models available in both colors




**GR404-W GR404-N**



**GR405-W GR405-N**



**GR406-W GR406-N**



4 season indoor/outdoor speakers



Wall/ceiling mounting brackets included



Weather-resistant, UV protected and hermetically sealed cabinets with durable rust-proof aluminum grills



Spring loaded binding posts



(Dual voice-coil single stereo speakers)

**GR405S-W**



**GR405S-N**

Model	System	Woofer (inches)	Tweeter (inches)	Suggested Amplifier (watts)	Frequency Response	Impedance (Ohms)	Sensitivity (dB)	Weight ea (kg / lb)	Unit Dimensions (H x W x D) (cm / inches)
GR404	2-way	4	½	15 ~ 50	80 ~ 20 kHz	8	88	1.4 / 3	20 x 12.5 x 16 / 8 x 5 x 6¼
GR405	2-way	5¼	½	15 ~ 100	50 ~ 20 kHz	8	89	2.7 / 7	23 x 15 x 19 / 9 x 6 x 7½
GR405S	2-way	Dual voice coil 5¼	2 x 1	15 ~ 100	40 ~ 20 kHz	8	88	2.8 / 7.2	28.5 x 17 x 20 / 11¼ x 6¾ x 7¾
GR406	2-way	6½	1	15 ~ 100	40 ~ 20 kHz	8	91	2.8 / 6.2	28.5 x 19 x 20 / 11¼ x 7½ x 7¾



The practical and versatile **GRANITE 400 series** can be used for both indoor and outdoor applications. The weather-resistant cabinets, made of glass-reinforced polypropylene, can easily be installed around the house and throughout the garden. All models are available in black or white, to suit any decor and can be wall or ceiling mounted using the supplied brackets.

### Outdoor Weather-Proof Volume Controls

### Weather-Proof Transformer



**ACC102**

(70 W)



**OVC100-G**

(100 W)



**QET-20**

- Hook any speaker to the weatherproof QET20 transformer for a 70 volt option
- Tap adjusts at 70V to 5, 10, 15 or 20 watt or 8 Ohms.



**GR308-N**

(Available only in black)



**GR405T-N**

**GR405T-W**

Built-in 70 volt transformer with 4, 8, 16, 30 watt and 8 Ohm tap switch

Model	System	Woofer (inches)	Tweeter (inches)	Suggested amplifier (watts)	Frequency Response	Impedance (Ohms)	Sensitivity (dB)	Weight ea (kg / lb)	Unit Dimensions (H x W x D) (cm / inches)
GR405T	2-way	5¼	1	15 ~ 100	40 Hz~20 kHz	70/100V or 8Ω	88	2.2/4.9	23 x 14 x 16 / 9 x 5½ x 6¼
GR308-N	2-way	8	1	15 ~ 125	28 Hz ~22 kHz	8	86	2.2/5	36.5 x 27.5 x 27 / 14¼ x 11 x 10¾